



**FORM: 135-TECH.ENG**

**PAGE 1 OF 2**

**TECHNICAL INFORMATION - TYPICAL ANALYSIS**

**PRODUCT: CANTESCO® LEAK DETECTION COMPOUND - MID TEMPERATURE**

**APPLICATION:** Mid temperature solution for detection of leaks in compressed air and gas systems. Green solution allows for easier leak location against reflective surfaces such as aluminum and stainless steel. Includes viscosity additive to allow for adherence to vertical surfaces. For regular temperature applications (to +27°F / -3°C) use CANTESCO® FORMULA 100, request 100-TECH for additional information.

**COMPOSITION:** Product does not contain mineral oil, vegetable oil, animal oil or fats; any material that will ignite or explode when in contact with liquid or gaseous oxygen; materials that will act as primary skin irritants, skin sensitizers or produce any other dermatosis; ketones, aldehydes, and alcohols as components in the formulation.

**TEMP RANGE:** -35°F TO 200°F (-37°C TO 93°C)

**PACKAGING:** Ready to use format available in 8 oz bottles with 12" extension tube in each bottle, 1 gallon, 5 gallon and 55 gallon drums.

ITEM	CODE	SIZE	QUANTITY PER BOX
135-08	00010	8 oz bottle	12 bottles per box
135-1G	10310	1 gallon jug	4 jugs per box
135-5G	10315	5 gallon pail	per pail
135-DR	10320	55 gallon drum	per drum

**MSDS:** An MSDS is available for this product upon request. To receive a copy e-mail us at [msds@cantesco.com](mailto:msds@cantesco.com) and request an MSDS for FORMULA 135.

PLEASE NOTE: Product use and conditions of use are beyond the control of CANTESCO CORPORATION. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results are the responsibility of the end-user. No other warranties, expressed or implied, are made.

LEAK DETECTION COMPOUNDS    GAS LEAK DETECTORS    ZINC RICH SPRAY GALVS  
DYE PENETRANT INSPECTION    ANTI-SPATTERS    NOZZLE TIP DIP    WIRE LUBE PADS  
COOLING FLUIDS    STAINLESS STEEL PICKLING PASTE    ALUMINUM CLEANER



FORM: 135-TECH.ENG

PAGE 2 OF 2

### TECHNICAL INFORMATION - TYPICAL ANALYSIS

#### SPECIFICATIONS:

TEST	RESULTS	METHOD
Foreign Matter	clear & free from suspended matter/sediment	MIL-PRF-25567E (sec 4.2.2.1)
Odor	No objectionable odor	ASTM D1292
pH	7.0 (+/-0.5) neutral range	MIL-PRF-25567E (sec 4.2.2.3)
Nonflammability	nonflammable	ASTM D92
Leak Detection	Immediate foaming	MIL-PRF-25567E (sec 4.2.2.5)
Foaming Ability	Initial > 145.0 mm Final > 130.0 mm	ASTM D1173
Freezing Point	-35°F to 200°F (-37°C to 93°C)	ASTM D1177
Residue	Less than 1.00 percent by weight	MIL-PRF-25567E (sec 4.2.2.8)
Corrosion	No corrosion on test panels	MIL-PRF-25567E (sec 4.2.2.9)
Mold Growth	Does not support mold growth	MIL-PRF-25567E (sec 4.2.2.11)
Sulphur	< 000.60 ug/gram	ASTM D-129 / D-516 (B)
Fluoride	< 010.50 ug/gram	ASTM D-808 / D-1179 (B)
Chloride	< 155.00 ug/gram	ASTM D-808 / D-512 (C)
Ammonia	No ammonia	ASTM D1426

#### Q&A:

For answers on how to use CANTESCO® LEAK DETECTION COMPOUNDS ask for a copy of our LEAK TESTING IN WELDING APPLICATIONS booklet. For a complete product listing request a copy of our WELDING PRODUCTS CATALOG.

To receive a copy of Military specification please contact [www.document-center.com](http://www.document-center.com). For a copy of ASTM test methods for halogen and chloride content (sulphur, fluoride and chloride) contact the ASTM at [www.astm.org](http://www.astm.org). For further links visit us at [www.cantesco.com](http://www.cantesco.com)

PLEASE NOTE: Product use and conditions of use are beyond the control of CANTESCO CORPORATION. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results are the responsibility of the end-user. No other warranties, expressed or implied, are made.

LEAK DETECTION COMPOUNDS    GAS LEAK DETECTORS    ZINC RICH SPRAY GALVS  
DYE PENETRANT INSPECTION    ANTI-SPATTERS    NOZZLE TIP DIP    WIRE LUBE PADS  
COOLING FLUIDS    STAINLESS STEEL PICKLING PASTE    ALUMINUM CLEANER