



FORM: SSL-TECH.ENG
PAGE 1 OF 1

TECHNICAL INFORMATION - TYPICAL ANALYSIS

PRODUCT: CANTESCO® GENERAL PURPOSE SILICONE LUBRICANT

APPLICATION: CANTESCO® SSL is suitable for general lubrication and release of dissimilar materials applications. It is an anti-stick agent that provides basic rust protection and has water displacing properties. CANTESCO® SSL is effective from -40°F to +400°F and is water white, clean and lubricates without oiliness.

CANTESCO® SSL is also an effective O-ring release in mechanical rubber molding. Can be used as a slip or release agent for wire or cable and as a release agent in molding and/or laminating methacrylate, acrylic, melamine, phenolics, polyethylene, polycarbonate and nylon.

COMPOSITION: Does not contain chlorinated solvents such as methylene chloride or materials such as xylene or ethylene glycol monobutyl ether.

PACKAGING: Ready to use format available in convenient aerosol cans.

ITEM	CODE	SIZE	QUANTITY PER BOX
SSL-20A	11750	20 oz aerosol cans	12 cans per box

MSDS: An MSDS is available for this product upon request. To receive a copy e-mail us at msds@cantesco.com and request an MSDS for SSL GENERAL PURPOSE SILICONE LUBRICANT.

SHELF LIFE: Shelf life for SSL-20A is currently one year from date of manufacture. Lot number is in human readable form (YYYY/MM/DD).

Q&A: For a complete product listing request a copy of our INDUSTRIAL AND INSTITUTIONAL CHEMICAL PRODUCTS CATALOG. For further information visit us at www.cantesco.com.

PLEASE NOTE: Product use and conditions of use are beyond the control of CANTESCO CORPORATION. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results are the responsibility of the end-user. No other warranties, expressed or implied, are made. For further details on our terms and conditions request a copy of our form QSF 319 New Account Package.

CITRUS ORANGE CLEANERS • GENERAL PURPOSE SILICONE LUBRICANT • FOOD GRADE SILICONE LUBRICANT
ELECTRO CONTACT CLEANER – NON FLAMMABLE • MOLY GEAR LUBRICANT • HEAVY DUTY MOLY PENETRANT
ALL METAL TAPPING & DRILLING FLUID